



## GENERAL INFORMATION

Power:	20W	30W	40W	60W
Colour temperature:	3000 / 4000K	3000 / 4000K	3000 / 4000K	3000 / 4000K
Total luminous flux:	2100lm	3150lm	4200lm	6300lm
Luminaire efficiency:	105lm/W	105lm/W	105lm/W	105lm/W
Fixture colour:	RAL9007 (gray)	RAL9007 (gray)	RAL9007 (gray)	RAL9007 (gray)
Fixture material:	Die-cast aluminum	Die-cast aluminum	Die-cast aluminum	Die-cast aluminum
Shielding:	PMMA	PMMA	PMMA	PMMA
Ambient working temperature:	-35°C~50°C	-35°C~50°C	-35°C~50°C	-35°C~50°C
Protection class:	IP65	IP65	IP65	IP65
Isolation class:	Class II	Class II	Class II	Class II
Impact protection class:	IK09 (alu) IK08 (PMMA)	IK09 (alu) IK08 (PMMA)	IK09 (alu) IK08 (PMMA)	IK09 (alu) IK08 (PMMA)
Frequency:	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Colour rendering index:	CRI 83 / 75	CRI 83 / 75	CRI 83 / 75	CRI 83 / 75
Voltage:	220-240V	220-240V	220-240V	220-240V
Effect factor:	>0,9	>0,9	>0,9	>0,9
Driver:	Internal	Internal	Internal	Internal
Driver power:	700mA	700mA	700mA	700mA
Lifespan L90B10:	100.000 hours	100.000 hours	100.000 hours	100.000 hours
Dimable:	Yes	Yes	Yes	Yes
Dimming method:	Night-drop (8h 50%)	Night-drop (8h 50%)	Night-drop (8h 50%)	Night-drop (8h 50%)
Assymetrical optic:	Yes (by request)	Yes (by request)	Yes (by request)	Yes (by request)
CLO-system:	Yes (by request)	Yes (by request)	Yes (by request)	Yes (by request)
Mounting:	Ø76 pole*	Ø76 pole*	Ø76 pole*	Ø76 pole*
Weight:	9,8 kg	9,8 kg	9,8 kg	9,8 kg
Product no:	3000K 4000K	01-0110-000170 01-0110-000171	01-0110-000172 01-0110-000173	01-0110-000174 01-0110-000175
				01-0110-000176 01-0110-000177

\*By request with reduction ring for Ø:60 pole mounting

