



GENERAL INFORMATION

Power:	20W	30W	40W	60W	
Colour temperature:	3000 / 4000K	3000 / 4000K	3000 / 4000K	3000 / 4000K	
Total luminous flux:	1670 / 1980lm	2540 / 2970lm	3370 / 3660lm	4970 / 5400lm	
Luminaire efficiency:	99lm/W (4000K)	99lm/W (4000K)	99lm/W (4000K)	98lm/W (4000K)	
Fixture colour:	RAL9007 (Gray)	RAL9007 (Gray)	RAL9007 (Gray)	RAL9007 (Gray)	
Fixture material:	Die-cast aluminum	Die-cast aluminum	Die-cast aluminum	Die-cast aluminum	
Shielding:	PMMA	PMMA	PMMA	PMMA	
Ambient working temperature:	-35°~50°	-35°~50°	-35°~50°	-35°~50°	
Protection class:	IP65	IP65	IP65	IP65	
Impact protection class:	IK09 (alu) IK08 (PMMA)	IK09 (alu) IK08 (PMMA)	IK09 (alu) IK08 (PMMA)	IK09 (alu) IK08 (PMMA)	
Isolation class:	Class II	Class II	Class II	Class II	
Frequency:	50Hz	50Hz	50Hz	50Hz	
Colour rendering index:	CRI >70	CRI >70	CRI >70	CRI >70	
Voltage:	100-240VAC	100-240VAC	100-240VAC	100-240VAC	
Effect factor:	>0,9	>0,9	>0,9	>0,9	
Driver:	Internal	Internal	Internal	Internal	
Driver power:	700mA	700mA	700mA	700mA	
Dimable:	Yes	Yes	Yes	Yes	
Dimming method:	Night-drop (8h 50%)	Night-drop (8h 50%)	Night-drop (8h 50%)	Night-drop (8h 50%)	
Lifespan L70B50:	70.000 hours	70.000 hours	70.000 hours	70.000 hours	
Weight:	10,55kg	10,55kg	10,55kg	10,94kg	
Dimensions (mm):	Ø:495,8 x H:650,9	Ø:495,8 x H:650,9	Ø:495,8 x H:650,9	Ø:495,8 x H:650,9	
Humidity during operation:	20-90%	20-90%	20-90%	20-90%	
Mounting:	Ø:89 pole	Ø:89 pole	Ø:89 pole	Ø:89 pole	
Product no.:	Grå / 3000K Grå / 4000K	01-0110-000178 01-0110-000179	01-0110-000180 01-0110-000181	01-0110-000182 01-0110-000183	01-0110-000185 01-0110-000186